

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name FLITECELL LITHIUM BATTERY PACK

Synonyms FLITECELL EXPLORE TI, 50.4V, 40AH, 2016WH • FLITECELL NANO TI, 50.4V, 16AH, 806WH • FLITECELL SPORT TI SERIES 2.2, 50.4V, 29.4AH, 1482WH • FLITECELL SPORT TI SERIES 3, 50.4V, 29.4AH, 1482WH • MN FLITECELL EXPLORE, 50.4V, 40AH, 2016WH • MN FLITECELL NANO, 50.4V, 16AH, 806W • MN FLITECELL SPORT, 50.4V, 29.4AH, 1482WH

1.2 Uses and uses advised against

Uses LITHIUM BATTERY
Used in Personal Watercraft

1.3 Details of the supplier of the product

Supplier name FLITEBOARD (NZ)
Address 4/18 Banksia Drive, Byron Bay, NSW, 2481, AUSTRALIA
Telephone Not supplied.
Email support@fliteboard.com

1.4 Emergency telephone numbers

Chemtrec NZ +64 9-801 0034
Toll Free NZ 0800 425 459

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

HAZARDOUS ACCORDING TO NZ ENVIRONMENTAL PROTECTION AUTHORITY CRITERIA

Physical Hazards

Not classified as a Physical Hazard

Health Hazards

Acute Toxicity: Inhalation: Category 3
Acute Toxicity: Oral: Category 3
Carcinogenicity: Category 2
Germ Cell Mutagenicity: Category 1
Serious Eye Damage / Eye Irritation: Category 1
Skin Corrosion/Irritation: Category 1A
Skin Sensitisation: Category 1
Specific Target Organ Toxicity (Repeated Exposure): Category 1
Toxic to Reproduction: Category 1B

Environmental Hazards

Aquatic Toxicity (Chronic): Category 2

2.2 GHS Label elements

Signal word DANGER

Pictograms



PRODUCT NAME FLITECELL LITHIUM BATTERY PACK**Hazard statements**

H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H340	May cause genetic defects.
H351	Suspected of causing cancer.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Prevention statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

Storage statements

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

2.3 Other hazards

NOTE: Hazard statement relates to battery contents. Potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically, physically or electrically abused.

3. COMPOSITION/ INFORMATION ON INGREDIENTS**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content
ALUMINIUM	7429-90-5	231-072-3	<50%
COBALT LITHIUM DIOXIDE	12190-79-3	235-362-0	<50%
MANGANESE	7439-96-5	231-105-1	<50%
NICKEL	7440-02-0	231-111-4	<50%
DIMETHYL CARBONATE	616-38-6	210-478-4	<20%
ETHYL CARBONATE	105-58-8	203-311-1	<20%
ETHYL METHYL CARBONATE	623-53-0	613-014-2	<20%
ETHYLENE CARBONATE	96-49-1	202-510-0	<20%
PROPYLENE CARBONATE	108-32-7	203-572-1	<20%
CARBON BLACK	1333-86-4	215-609-9	<18%
COPPER	7440-50-8	231-159-6	9 to 18%
GRAPHITE	7782-42-5	231-955-3	<18%
LITHIUM HEXAFLUOROPHOSPHATE(1-)	21324-40-3	244-334-7	1 to 5%
INERT MATERIAL(S)	-	-	Remainder

PRODUCT NAME FLITECELL LITHIUM BATTERY PACK

POLYVINYLIDENE FLUORIDE

24937-79-9

607-458-6

<1%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	Exposure is considered unlikely unless casing is damaged. Flush gently with running water. Seek medical attention if irritation develops.
Inhalation	Exposure is considered unlikely. Due to product form / nature of use, an inhalation hazard is not anticipated.
Skin	Exposure is considered unlikely unless casing is damaged. Gently flush affected areas with water. Seek medical attention if irritation develops.
Ingestion	For advice, contact the National Poisons Centre on 0800 764 766 (0800 POISON) or +643 479 7248 or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.
First aid facilities	Eye wash facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

Adverse effects not expected from this product during normal use. However, exposure to battery contents may cause irritation and potential burns.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent. Do NOT use water. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Contents react with water. May explode if exposed to high temperatures due to pressure build up in battery casing. Lithium may burn in a fire situation and may be ejected from the battery. Damaged cells may evolve toxic and flammable vapours.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

2Y
2 Fine Water Spray.
Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

If spilt, collect and reuse where possible. If battery is broken or damaged, absorb liquid with sand or similar. Contain spillage, then collect and place in suitable containers for disposal. CAUTION: Avoid exposure to contents.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

PRODUCT NAME FLITECELL LITHIUM BATTERY PACK

7.2 Conditions for safe storage, including any incompatibilities

Store tightly sealed in a cool, dry, well ventilated area, removed from water, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Store between -10°C and 30°C.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Aluminium metal and insoluble aluminium compounds (including pyro powder, aluminium oxide, and aluminium welding fumes), as Al	WES [NZ]	--	1	--	--
Carbon black	WES [NZ]	--	3	--	--
Copper and its inorganic compounds, as Cu	WES [NZ]	--	0.01	--	--
Copper and its inorganic compounds, as Cu	WES [Proposed]	--	0.01	--	--
Graphite, all forms except graphite fibres	WES [NZ]	--	3	--	--
Manganese fume, dust and compounds, as Mn	WES [NZ]	--	0.2	--	--
Manganese fume, dust and compounds, as Mn (resp.)	WES [NZ]	--	0.02	--	--
Nickel, elemental or metallic	WES [NZ]	--	0.005	--	--
Nickel, inorganic compounds	WES [NZ]	--	0.05	--	--
Nickel, inorganic compounds (respirable dust)	WES [NZ]	--	0.005	--	--

Biological limits

Ingredient	Determinant	Sampling Time	BEI
COBALT LITHIUM DIOXIDE	Cobalt in urine	End of shift at end of workweek	15 µg/L
POLYVINYLIDENE FLUORIDE	Fluoride in urine	Prior to shift	2 mg/L
	Fluoride in urine	End of shift	3 mg/L

Reference: ACGIH Biological Exposure Indices

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas.

PPE

Eye / Face	Not required under normal conditions of use.
Hands	Wear PVC or rubber gloves.
Body	Not required under normal conditions of use.
Respiratory	Not required under normal conditions of use.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	SILVER AND BLACK PRISMATIC SOLID
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE

PRODUCT NAME FLITECELL LITHIUM BATTERY PACK

9.1 Information on basic physical and chemical properties

Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Heat above 70°C or incinerate. Deform. Mutilate. Crush. Pierce. Disassemble. Overcharge. Short circuit. Expose over a long period to humid conditions.

10.5 Incompatible materials

Battery contents are incompatible with water (evolving flammable gas), oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Batteries consist of a hermetically sealed metallic container containing a number of chemicals and materials of construction that may be hazardous upon release. Over exposure considered unlikely unless battery ruptures and contact with contents occurs. Contents may be harmful. Toxic if swallowed or if inhaled.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
MANGANESE	9000 mg/kg (rat)	--	> 5.14 mg/L/4hrs (rat)
NICKEL	> 9000 mg/kg (Sprague-Dawley rat)	--	--
DIMETHYL CARBONATE	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)	> 5.36 mg/L/4hrs (rat)
ETHYL CARBONATE	> 4,876 mg/kg (rat)	--	> 1.268 mg/l/7hrs (rat)
ETHYLENE CARBONATE	10 g/kg (rat)	> 3 g/kg (rabbit)	--
PROPYLENE CARBONATE	20.7 g/kg (mouse)	> 20 mL/kg (rabbit)	--
CARBON BLACK	> 10,000 mg/kg (rat)	--	--
COPPER	--	> 2000 mg/kg (rat)	--
LITHIUM HEXAFLUOROPHOSPHATE(1-)	> 50 - 300 mg/kg (rat)	--	--

Skin Battery contents may be corrosive and cause irritation, redness, dermatitis and possible skin burns. Exposure is considered unlikely unless the battery ruptures.

PRODUCT NAME FLITECELL LITHIUM BATTERY PACK

Eye	Battery contents may be corrosive and cause irritation, redness and possible eye burns. Exposure is considered unlikely unless the battery ruptures.
Sensitisation	Exposure to contents may cause skin sensitisation. This product is not classified as a respiratory sensitiser.
Mutagenicity	Battery contents may cause genetic defects.
Carcinogenicity	Due to the product encapsulation, exposure to contents is not anticipated with normal use. However, the battery contains contents which may be carcinogenic.
Reproductive	Exposure to contents containing cobalt may damage fertility.
STOT - single exposure	Not classified as causing organ damage from single exposure. Due to the product form and nature of use, exposure to internal contents is not anticipated unless the battery ruptures. Exposure to contents may cause respiratory irritation.
STOT - repeated exposure	Due to the product form and nature of use, exposure to internal contents is not anticipated unless the battery ruptures. Some battery contents have the potential to cause damage through repeated exposure, however such exposure is considered unlikely.
Aspiration	Not relevant.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

This product may be hazardous to the environment if not properly used or disposed of. Do not let internal components enter the marine environment. Avoid release to waterways, wastewater or ground water.

12.2 Persistence and degradability

This product is not readily biodegradable.

12.3 Bioaccumulative potential

Limited information was available at the time of this review.

12.4 Mobility in soil

This product has low mobility in soil.

12.5 Other adverse effects

Avoid contamination of drains and waterways.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Reuse or recycle where possible. Return to manufacturer/supplier. Contact your state EPA or the manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD ACCORDING TO LAND TRANSPORT RULE: DANGEROUS GOODS 2005, IMDG AND IATA



	LAND TRANSPORT (NZS 5433)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	3480	3480	3480
14.2 Proper Shipping Name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)	LITHIUM ION BATTERIES (including lithium ion polymer batteries)	LITHIUM ION BATTERIES (including lithium ion polymer batteries)
14.3 Transport hazard class	9A	9A	9A
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Marine Pollutant.

14.6 Special precautions for user

Hazchem code	2Y
EmS	F-A, S-I
Other information	The environmentally hazardous substance mark is not required when transported in packages of less than 5 kg/L (UN Model Regulations: Special Provision 375; IATA: Special Provision A197; IMDG: Special Provision 969). UN number 3481 applies for LITHIUM BATTERIES CONTAINED IN EQUIPMENT or LITHIUM BATTERIES PACKED WITH EQUIPMENT which may also apply to this product.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Approval code	MANUFACTURED ARTICLE
Group standard	Something for which its intended use is primarily to do with its physical shape, rather than its chemical composition.
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) Some components are listed on AIIC, or are exempt. NEW ZEALAND: NZIoC (New Zealand Inventory of Chemicals) All components are listed on the NZIoC inventory, or are exempt.

16. OTHER INFORMATION

Additional information	<p>EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES: Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).</p> <p>WORKPLACE CONTROLS AND PRACTICES: Unless a less toxic chemical can be substituted for a hazardous substance, ENGINEERING CONTROLS are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.</p> <p>PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.</p> <p>HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.</p>
-------------------------------	---

PRODUCT NAME FLITECELL LITHIUM BATTERY PACK**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CCID	Chemical Classification and Information Database (HSNO)
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
EPA	Environmental Protection Authority [New Zealand]
GHS	Globally Harmonized System
HSNO	Hazardous Substances and New Organisms
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmtglobal.com
Web: www.rmtglobal.com

[End of SDS]